



Website (网址) Factory (工厂)

厂址: 山东青岛平度市明村镇马戈庄工业区
Magezhuang Industrial Park,
Pingdu, Qingdao, China
电话: +86 0532 86331056 86339888
+86 13506421529
网址: www.macsuntyre.com
www.maoxiangtyre.com
邮箱: yshmlytex@126.com



Website (网址) Export department (外贸部)

外贸部/Export Department
地址/Add: 青岛市崂山区资源博雅4号楼402
No.402, Buliding 4, Resources
BoYa Plaza, Laoshan Dist.
Qingdao.China
电话/Mob: +86 0532 66655897
+86 18567009825
邮箱/Email: postmaster@maoxiangtyre.com



**QINGDAO
MAOXIANG
RUBBER CO., LTD.**
青岛茂祥橡胶有限公司



全国统一服务热线
400-669-0175

GRANDPEAK

COMPANY PROFILE

公司简介

2002

Established in 2002

63270

Covering an area
of 63270 m²

1.2

Annual output of
1.2 million sets

青岛茂祥橡胶有限公司位于山东省青岛平度市明村镇，成立于2002年，占地63270平方米，总资产2亿多元，年产量120万套，属国内大中型斜交轮胎生产工厂。

工厂主要产品包括工程机械轮胎，工业轮胎，叉车轮胎，农业轮胎，农机具轮胎，矿山轮胎，轻卡及载重轮胎等，所有产品均已通过ISO9001,CCC,DOT等认证。依赖雄厚的技术实力和产能优势，我们已出口到东南亚，中东，欧洲，非洲，美洲等全球70个国家和地区，深受客户信赖和好评。

Qingdao Maoxiang Rubber Co., Ltd. is located in Mingcun Town, Qingdao, China. It was established in 2002, covers an area of 63270 square meters, total assets of more than 200 million yuan, the annual output is 1.2 million sets of tyres. It is a large and medium-sized diagonal tire production factory in China. Factory products series include OTR tyres, industrial tyres, forklift tyres, agricultural tyres, implement tyres, mining and truck tyres, etc. All products have passed ISO9001, CCC, DOT and other certifications. Relying on our strong technical strength and production capacity advantages, we have exported to 70+ countries and regions around the world, including Southeast Asia, Middle East, Europe, Africa and Americas, and we have won high reputation and recognition from global customers.

- OTR
非公路
- IND
工业
- AGR
农业/农机具
- ATV
全地形
- MINING & TRUCK
矿山/卡车

Qingdao Maoxiang Rubber Co., Ltd. - Your Trusted Partner in Specialty Tyres

青岛茂祥橡胶有限公司-特种轮胎行业值得信赖的合作伙伴

QUALIFICATION CERTIFICATE

资质证书



FACTORY FLOOR

生产车间/厂区一角



CONTENTS

目录

1. OFF THE ORAD TYRE	01
E-3/L-3, L-5, G-2/L-2, R-3, ADVAN X	
2. INDUSTRIAL TYRE	05
R-4, R-4B, R-4C, EXCAVATOR, FORKLIFT, SOLID, SKS-1,2,3,4,5,6	
3. AGRICULTURAL TYRE	10
R-1, R-2, PR-1, F-2	
4. IMPLEMENT TYRE	13
IMP100, F-3, I-1, I-3	
5. ATV TYRE	14
ATV-1, ATV-2	
6. MINING & TRUCK TYRE	16
M01, M02, M03, T01, T02	



OTR (非公路)

用于要求苛刻的建筑和采矿设备

OTR
非公路

IND
工业

AGR
农业/农机具

ATV
全地形

MINING & TRUCK
矿山/卡车



L-5

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD		相应气压(KPA) PRESSURE		有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	50km/h	10km/h	50km/h	10km/h		
16/70-20	16	42	13	410	1090	/	2925		350	TT/TL	L-5
20.5/70-16	14	41	10.00G	356	955	/	1800	/	390		
17.5-25	24	52	14.00/1.5	445	1400	5600	8250		575		
23.5-25	28	72	19.50/2.5	595	1675	8000	12500	350	475		



G-2/L-2

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD		相应气压(KPA) PRESSURE		有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	30km/h	10km/h	30km/h	10km/h		
13.00-24	12	24.5	8.00TG	333	1278	2725	5600	300	450	TT/TL	G-2/L-2
14.00-24	16	25.5	8.00TG	362	1348	3650	7300	350	550		
17.5-25	16	26.5	14.00/1.5	445	1350	4250	7300	300	475		
20.5-25	16	28.5	17.00/2.0	521	1493	/	4500	/	350		



R-3



ADVAN X

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压(KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
23.1-26	14	16	DW20	595	1500	5600	230	TT/TL	R-3
17.5-25	16	20	10.0SDC	445	1320	8250	575	TT	ADVAN X

USED FOR DEMANDING CONSTRUCTION
AND MINING EQUIPMENT
用于要求苛刻的建筑和采矿设备



E-3/L-3A



E-3/L-3B

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD		相应气压(KPA) PRESSURE		有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	50km/h	10km/h	50km/h	10km/h		
7.50-16	12	14	6.00G	215	820	/	1740	/	670	TT/TL	E-3/L-3A
8.25-16	14	15	6	235	865	/	1740	/	670		
1200-16	16	17	7	259	900	/	2090	/	630		
14/90-16	14	17	6.5	300	930	/	1650	/	420		
20.5-16	16	17.5	6.50H	340	890	/	1650	/	390		
20.5/70-16	16	21	10.00F	350	900	/	1650	/	390		
23.5/70-16	16	18.5	6.50H	350	900	1650	1650	390	390		
16/70-20	18	22	13(SDC)	410	1070	2925	2925	350	350		
16/70-24	18	22	13(SDC)	410	1170	3760	3760	350	350		
14.00-24	20	24	10	375	1370	4625	8500	475	700		
16.00-24	24	26	11.25	430	1495	5450	9750	400	550	TT/TL	E-3/L-3A、B
15.5-25	16	24	12.00/1.3	395	1275	3750	6500	325	525		
17.5-25	16	25	14.00/1.5	445	1350	4250	7300	300	475		
	20	28	14.00/1.5	445	1350	5000	8250	400	575		
20.5-25	20	29	17.00/2.0	520	1490	5450	8250	275	350		
	24	29	17.00/2.0	520	1490	6000	9500	325	450		
23.5-25	20	31	19.50/2.5	595	1615	6150	9500	225	300		
	24	31	19.50/2.5	595	1615	7300	10900	300	375		
26.5-25	24	35	22.00/3.0	675	1750	9250	14000	625	400	TT/TL	E-3/L-3A、B
	28	35	22.00/3.0	675	1750	8250	13000	375	300		
29.5-25	28	38	25.00/3.5	750	1875	11500	17500	325	425		
	32	38	25.00/3.5	750	1875	13600	19500	425	525		



IND (工业)
用于物料搬运和仓库车辆

OTR 非公路	IND 工业	AGR 农业/农机具	ATV 全地形	MINING & TRUCK 矿山/卡车
------------	-----------	---------------	------------	-------------------------



SKS-1



SKS-1 New

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
10-16.5	10	16	8.25	264	773	2135	520	TL	SKS-1
12-16.5	12	21	9.75	307	831	2820	550		
14-17.5	14	21	10.5	350	922	3875	550		
23*8.5-12	6	13	7.00	213	574	820	340		
11L-16	12	16	8.00	279	838	1250	440		
27*8.5-15	10	12	7.00	183	657	900	500		



SKS-2



SKS-3



SKS-4



SKS-5



SKS-6

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
12-16.5	14	27	9.75	314	845	3075	620	TL	SKS-2, 3, 4, 5
12-16.5	14	32	9.75	314	795	3075	620		
10-16.5	12	22	8.25	270	785	2135	520	TL	SKS-3, 4, 5, 6
10-16.5	12	27	8.25	270	785	2135	520		



R-4

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
16.9-24	12	25	15	430	1335	3250	260	TL	R-4
16.9-28	12	25	15	430	1435	3450	260		
17.5L-24	12	25	15	445	1265	2800	220		
18.4-26	12	25	16	467	1450	4000	250		
19.5L-24	12	26	17	495	1340	3500	230		
21L-24	14	27	18	533	1400	3875	220		



R-4B

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
19.5L-24	12	26	17	495	1340	3455	230	TL	R-4B



R-4C

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
10.5/80-18	12	22	9.0	274	885	2140	440	TL	R-4C
12.5/80-18	12	22.5	9.0	350	1001	2625	370		



EXCAVATOR



规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
9.00-20	16	19	7.0	259	1038	2900	880	TT	EXCAVATOR
10.00-20	16	19	7.5	278	1055	3000	810		



SD-1



SD-2

规格 SIZE	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		负荷 LOAD CAPACITY (KG) 叉车 BALANCE FORKLIFT				花纹 PATTERN
		断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	10km/h		16km/h		
				驱动 Drive	导向 Steer	驱动 Drive	导向 Steer	
15X4 1/2-8	3.25/3.0	106	380	905	725	675	655	SD-1/SD-2
5.00-8	3.0	137	469	1210	930	950	800	
18X7-8	4.33	165	457	2350	1880	2265	1700	
21X8-9	6.0	189	535	2810	2250	2715	2035	
6.00-9	4.0	140	545	1920	1535	1855	1390	
6.50-10	5.0	157	597	1545	1455	2360	1910	
7.00-12	5.0	168	683	3015	2410	2910	2185	
28X9-15 8.15-15	7.0	207	706	4090	3270	3945	2960	
8.25-15	6.5	205	847	4940	3950	4765	3575	
300-15	8.0	258	838	5990	4700	5780	4335	

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATT ERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	25km/h	25km/h		
5.00-8	10	10	3.50D	137	470	1170	900	TT	FORK LIFT
6.00-9	10	11.5	4.00E	160	540	1795	850		
6.50-10	10	13.5	5.00F	175	590	1625	850		
7.00-12	12	15	5.00S	190	683	2555	850		
28X9-15 8.15-15	14	17	7.0	220	710	2970	800		
8.25-15	14	17	6.5	236	847	4010	800		



FORKLIFT



AGR (农业)

为拖拉机和农业机械设计的

OTR

非公路

IND

工业

AGR

农业/农机具

ATV

全地形

MINING & TRUCK

矿山/卡车



R-1A



R-1B



R-1C



R-1D



R-1E

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压(KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	30km/h	30km/h		
12.4-28	12	29	W11	315	1260	1510	230	TT	R-1A/B/D
11.2-28	8	28	W10	285	1205	1305	240		R-1A
11.2-24	10	26	W10	285	1105	1380	300		R-1A
9.5-24	12	25	W8	240	1050	1110	280		R-1C
8.3-24	10	24	W7	210	995	810	240		R-1C
9.5-20	12	24	W8	240	950	955	280		R-1E
8.3-20	12	24	W7	210	895	760	240		R-1C
7.50-20	10	21	5.50F	205	910	760	210		R-1C
7.50-16	10	21	5.50F	205	810	650	210		R-1E
6.50-16	6	20	5.00F	180	765	565	250		R-1E
6.00-16	6	19	4.50E	165	745	495	250		R-1B
6.00-12	6	20	4.50E	165	640	405	250		R-1C



PR-1



R-2



R-2B



R-2C

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	30km/h	30km/h		
11.2-28	8	46	W10	285	1235	1305	240	TT	R-2
11.2-24	10	46	W10	285	1135	1380	300		R-2C
9.5-24	12	42	W8	230	1070	1110	280		R-2C
8.3-24	10	42	W7	210	1018	810	240		R-2C
7.50-20	12	37	5.50F	205	934	760	210		R-2C
7.50-16	10	37	5.50F	205	834	650	210		R-2/R-2C
6.00-16	8	27	4.50E	165	765	495	250		R-2B
6.00-14	8	27	4.50E	165	710	450	250		R-2B
6.00-12	8	27	4.50E	165	660	405	250		R-2B





F-2



F-2B



F-2C



F-2D

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER	30km/h	30km/h		
6.50-20	8	11	5.0F	180	860	865	420	TT	F-2
7.50-16	8	12	5.50F	205	810	870	370		F-2C
6.00-16	10	9	4.0E	160	740	755	450		F-2/F-2C
5.50-16	10	8	4.0E	150	710	675	420		F-2
5.00-16	10	8.5	3.0D	140	690	525	370		F-2B
5.00-15	8	8	3.0D	135	670	450	360		F-2B
4.50-16	6	8	3.0D	122	655	365	360		F-2
4.00-16	6	8	3.0D	110	640	365	360		F-2
4.50-14	10	8	3.0D	122	605	480	360		F-2
4.00-14	6	8	3.0D	110	590	270	340		F-2
4.00-12	6	8	3.0D	110	535	270	340	F-2	
7.60-15	8	8	5.50	175	750	950	360	TL	F-2D



规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATT ERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
10.0/75-15.3	12	9	9	254	750	1525	390	TT/TL	IMP100
10.0/80-12	12	9	9	254	710	1600	450		
23X8.5-12	6	9	7	205	535	655	230	TL	IMP100



IMP100



F-3

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATT ERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
11L-16	10	13.5	8LB	280	840	1240	340	TL	F-3



I-1

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATT ERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
10-15	8	12	8L13	276	855	1425	240	TT	I-1



I-3



I-3B



规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		最大负荷(KG) MAXIUM LOAD	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
400/60-15.5	16	20	13.00	450	874	2240	400	TT/TL	I-3
350/70-17.5	16	18	10.00F	350	890	1650	390	TT	I-3B
385/70-17.5	16	19	10.00F	356	900	1650	390	TT	I-3B
450/70-22.5	18	21.5	13(SDC)	410	1075	2925	350	TT	I-3B



ATV

专为全地形车辆设计的

OTR

非公路

IND

工业

AGR

农业/农机具

ATV

全地形

MINING & TRUCK

矿山/卡车



ATV-1



ATV-2

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		负荷(KG) LOADING	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
23X8.5-12	6	8.5	8.00L	225	595	655	230	TL	ATV-1
26X12.00-12	10	20	10.50L	310	670	1630	450	TL	ATV-1,2
31X15.5-15	8	14	13LB	385	780	1250	1250	TL	ATV-2
24X13.00-12	10	8	12.0	325	565	3087	207	TL	ATV-1



M01

M02

M03

MINING TYRE

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		负荷(KG) LOADING	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
7.50-16	16	19	6.0G	215	815	1500	730	TT	M01/M03
8.25-16	20	21.5	6.5H	235	865	1800	730		M01/M03
9.00-20	20	26	7	259	1018	4750	840		M02
11.00-20	18	20.5	8.5	293	1085	3650	910		M02
12.00-20	18	20.5	8.5	315	1125	3730	810		M02

MINING TYRE & TRUCK TYRE

矿山和卡车系列

OTR
非公路

IND
工业

AGR
农业/农机具

ATV
全地形

MINING & TRUCK
矿山/卡车



T01



T02

TRUCK TYRE

规格 SIZE	层级 PLY RATING	花纹深 (MM) TREAD DEPTH	标准轮辋 STANDARD RIM	新胎充气尺寸(MM) NEW INFLATED SIZES		负荷(KG) LOADING	相应气压 (KPA) PRESSURE	有无内胎 TT/TL	花纹 PATTERN
				断面宽 SECTION WIDTH	外直径 OVERALL DIAMETER				
4.50-12	10	8	3.0B	127	545	415	400	TT	T02
5.00-12	10	8	3.5B	143	568	485	400		T02
6.00-13	10	9	4.5J	170	655	655	420		T01/T02
6.00-14	10	9	4.5J	170	680	655	420		
6.00-15	10	9	4.5E	170	705	720	420		
6.50-15	10	10	4.5E	180	730	720	420		
6.50-16	12	10	5.5F	185	750	975	530		
7.00-15	12	11	5.50F	200	750	1040	530		
7.50-15	12	12	6.00G	215	780	1370	630		
7.00-16	12	11	5.5F	200	775	1220	630		
7.50-16	12	12	6.0G	215	805	1405	630		
8.25-16	14	13	6.5H	235	855	1705	630		
7.00-20	12	11	5.5	200	904	1580	740		
7.50-20	14	12	6	215	935	1885	810		
8.25-20	14	13	6.5	235	974	2205	810		
9.00-20	16	14	7	259	1018	2575	770		
10.00-20	16	14	7.5	278	1055	3000	810		
11.00-20	16	15	8	293	1085	3270	810		
12.00-20	18	16	8.5	315	1125	3730	810		
12.00-24	18	16	8.5	315	1225	4195	810		T01